

NATIONAL INSTITUTE OF OPEN SCHOOLING
(An autonomous Institution under Ministry of Education, Govt. of India)
A-24/25, Institutional Area, Sector-62, NOIDA – 201309
Website: www.nios.ac.in

File No.: F.42-1(7.9)/NIOS/Admn./Mtce

Date: 01/06/2026

NOTICE INVITING TENDER (LIMITED TENDER ENQUIRY)

Sealed quotations are invited from the identified contractors/firms for the following work

1. Name of Work:

Repair of Kitchen, Provision of Washing Area and Creation of Partition for R&I Section in front of PRO Office

2. Location of Work:

National Institute of Open Schooling, A-24/25, Sector-62, NOIDA – 201309 (U.P.)

3. Completion Time:

60 (Sixty) Days from the date of issue of Work Order.

4. Estimated Cost:

Rs. 5,72,892 (Rupees Five Lakh Seventy Two Thousand Eight Hundred Ninety Two Only), inclusive of all applicable taxes.

5. Tender Issue and Submission:

Particulars	Details
Tender Publishing Date	01.06.2026
Last Date & Time for Submission	22.06.2026 up to 14:00 hrs
Tender Opening Date & Time	Same day at 15:00 hrs
Place of Submission & Opening	Tender box placed in the Office of the Assistant Director (Mtce.), NIOS, A-24/25, Sector-62, NOIDA

6. Eligibility Criteria:

6.1 The bidder should have valid PAN and GST registration

6.2 The bidder should have successfully executed similar nature works (civil and electrical work) for Government Departments / PSUs / Autonomous Bodies during the last Seven years ending last day of month previous to the one in which applications are invited should be either of the following: -

- Three works each of at least **40%** of estimated cost, or

- Two works each of at least **50%** of estimated cost, or
- One work of at least **80%** of estimated cost.

6.3 The bidder should submit company profile.

6.4 The bidder should submit the audited balance sheets or audit reports for the last three financial years, the average turnover of the bidders should be at least 50 percent of the estimated cost.

6.5 The bidder should must submit the **Bid Security (Earnest Money Deposit): Rs. 11,458 /-** by FDR /Demand Draft/ Bank Guarantee in favor of Secretary, NIOS from a Nationalized Bank. MSME registered are exempted from EMD on submission of certificate.

7. Scope of Work:

The scope of work broadly includes (details at *Annexure A*):

- Dismantling works** including removal of portions of the existing false ceiling and dismantling of damaged components to access concealed AC conduits.
- Civil works** including making openings in brick masonry, minor brick work and disposal of debris.
- Flooring and wall finishing works** including ceramic wall tiles and cement concrete flooring repairs.
- Painting works** including acrylic distemper, exterior emulsion paint and aluminium paint.
- Partition works** including aluminium partition with glazing, ACP panels and aluminium door fittings for the R&I Section.
- Plumbing and drainage works** including CPVC water supply pipes, PVC drainage pipes and fittings for the washing area.
- Kitchen utilities** including installation of stainless steel kitchen sinks, bib cocks, angle valves and waste pipes.
- Ventilation system** including supply, installation and commissioning of a commercial kitchen exhaust chimney system.
- Other allied works** including construction of a manhole, sealing/repair of unused conduits and finishing works required for completion of the facility

8. Terms & Conditions:

8.1 The bidder must quote a consolidated price inclusive of all materials, labour, transportation, taxes, and installation.

8.2 No advance payment shall be made. Payment will be released only after satisfactory completion and certification by NIOS Engineer.

8.3 The work shall be completed strictly within the stipulated time.

8.4 The contractor shall ensure use of ISI-marked or approved quality materials.

8.5 NIOS reserves the right to accept or reject any or all quotations without assigning any reason.

8.6 Any damage to NIOS property during execution shall be rectified by the contractor at their own cost.

- 8.7 The measurements shall be recorded jointly with contractor and NIOS Engineer.
- 8.8 In case of delay, a penalty @1% per week shall be levied subject to a max of 5% of the contract value.
- 8.9 The contractor shall take all safety precautions for his workers and shall be sole responsible for any mishap.
- 8.10 **Bid Security (Earnest Money Deposit):** Rs. **11,458** /- by FDR /Demand Draft/ Bank Guarantee in favor of Secretary, NIOS from a Nationalized Bank. **MSME registered are exempted from EMD on submission of certificate.**
The EMD of successful bidder shall be returned only after receipt of Security Deposit.
Bids without EMD shall be summarily rejected. If bidders are MSME registered should submit the certificate of the same.
The EMD may be forfeited if:
(a) The bidder withdraws the offer during the validity period; or
(b) The successful bidder fails to sign the agreement or furnish the security deposit within the stipulated period.
- 8.11 **Performance Guarantee:** The successful bidders shall submit the performance Guarantee of 3% of the Contract Value as a FDR /Demand Draft/ Bank Guarantee from a Nationalized Bank, valid for one year Defect Liability Period plus 60 days.
- 8.12 All payments to the Contractor under this contract shall be made after deducting applicable taxes, duties, levies or statutory deductions as per prevailing Government rules and regulations.
- 8.13 **Dispute Resolution (Arbitration Clause):** Mandatory. Any dispute arising out of this contract shall be resolved through arbitration in accordance with the Arbitration and Conciliation Act, 1996, with the sole arbitrator appointed by the Chairman, NIOS. The arbitration shall be conducted in NOIDA, and the decision shall be binding on both parties. Furthermore, the court will be adjudicated as per the law of the land.
- 8.14 **Force Majeure Clause:** Mandatory. Neither party shall be liable for delays or non-performance due to unforeseen circumstances beyond their control (e.g natural disasters, war). The affected party must notify the other in writing within 7 days, and the contract period may be extended accordingly.
- 8.15 **Labour Welfare and Safety Measure:** The contractor shall adhere to all applicable labour laws, ensure necessary safety precautions for workers, and comply with NIOS's safety standards as per binding regulations.
- 8.16 **Non submission of Eligibility Criteria documents mentioned in para 6, the bid of the Firm / Firms will be summarily rejected.**
- 8.17 Late/unsealed/incomplete bids or bids received via fax/telegram/email shall not be accepted.
- 8.18 Bids received from uninvited bidders are treated as unsolicited and are not entertained; however unsolicited firms may be entertained in next round of tendering.

9. Submission Documents (As per Annexure B):

- 9.1 Signed and stamped copy of this NIT.
- 9.2 Quotation on firm's letterhead with unit rates and total cost
- 9.3 Copy of PAN card and GST registration.
- 9.4 List of similar works executed with copies of work orders or completion certificate in support of eligibility.
- 9.5 Declaration of acceptance of terms & conditions.

- 9.6 EMD in the form of FDR /Demand Draft/ Bank Guarantee / MSME Certificate
9.7 Audited balance sheets and audit reports for the last three financial years.

Sd/-

(Assistant Director (Mtce.))

National Institute of Open Schooling
A-24/25, Sector-62, NOIDA – 201309

Annexure A – Detailed Scope & Specifications

	Discription of Item	unit	qty
1	Making the opening in brick masonry including dismantling in floor or walls by cutting masonry and making good the damages to walls, flooring and jambs complete, to match existing surface including disposal of mulba/ rubbish to the nearest municipal dumping ground, all complete as per direction of Engineer-in-Charge	sqm	15
2	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	cum	5
3	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-inCharge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete (make somany / kajaria/orient bell)	sqm	50
5	Dismantling tile work in walls, floors and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm	sqm	50
6	Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge.	sqm	60
7	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gram/litre, of approved manufacturer and of required shade and colour all complete to achieve even shade and colour (two or more coats) over and including water thinnable priming coat with cement primer having VOC content less than 50 gram/litre	sqm	500
8	Finishing walls with ready mixed Premium acrylic emulsion paint (Company Depot Tinted) having VOC less than 50 gm/litre and UV resistance as per IS 15489:2004, Alkali & fungal resistance, dirt resistance exterior paint of required shade with silicon additives. Two or more coats applied @ 1.43 litre/ 10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm.	sqm	250
9	Painting with aluminium paint of approved brand and manufacture to give an even shade One or more coats .	sqm	60
10	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge	cum	2

11	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	sqm	10
12	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary lilling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass or stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket 31. 1. Powder coated aluminium (minimum thickness of powder coating 50 micron)	kg	30
13	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary lilling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass or stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :for fixed portion : Powder coated aluminium (minimum	kg	100

	thickness of powder coating 50 micron)		
14	Providing and fixing 2-3 mm thick Aluminium Composite Panel (ACP).	sqm	33
15	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge .(Cost of aluminium snap beading shall be paid in basic item):With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	sqm	25
16	Filling the gap in between aluminium frame & adjacent RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.Upto 5 mm depth and 5 mm width	m	50
17	Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm long with SS screws etc .complete as per direction of Engineer-in-Charge Polyester powder coated minimum thickness 50 micron aluminium tubular handle bar	each	6
18	Providing and fixing Brass 100 mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	each	4
19	Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISi, IS : 3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.	each	3
20	supply and fixing of 100mm pvc pipe including all fitting completeThis includes jointing of pipes & fittings with one step PVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete	m	25

21	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:6 (1 cement : 6 coarse sand) : With F.P.S.(non modular) bricks	cum	1
22	Providing and fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS:13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required : Kitchen sink with drain board 510x1040 mm bowl depth 225 mm	each	2
23	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings and fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc 20 mm nominal dia Pipes	m	45
24	Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms. 15 mm nominal bore	each	2
25	Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete	each	2
26	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15 mm nominal bore	each	2

27	Supplying, installing, testing, and commissioning of wall-mounted commercial kitchen exhaust chimney system complete as per specifications below (unit: each): Hood: SS 304 grade, 18-20 gauge (1.0-1.2 mm thick), rectangular canopy type, length 6-8 ft (specify 7 ft), width 3 ft, height 1.5-2 ft, #4 polished finish, with pre-wired LED lights (1 per 5 ft). Filters: SS baffle grease filters (washable, 25" high equivalent), with grease cup and drip tray. Exhaust Fan: metal exhaust fan 600mm crompton Ducting: SS/GI rectangular ducts (300x150 mm), 20-30 ft length with bends, insulated, including supports and exhaust collar (10-24" based on length). Installation: At 6.5-7 ft height from floor, with 3" standoff brackets, fire-safe per NFPA 96 equivalent, centrally above cooking range.	each	1
28	Constructing brick masonry manhole in cement mortar 1:4 (1 cement : 4 coarse sand) with R.C.C. top slab with 1:1.5:3 mix (1 cement : 1.5 coarse sand (zone-III) : 3 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design : Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) :With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	each	1

Covering Letter

To

The Secretary
National Institute of Open Schooling
A-24/25, Sector-62, Noida – 201309

Subject: Submission of Quotation for Limited Tender for **Repair of Kitchen, Provision of Washing Area and Creation of Partition for R&I Section in front of PRO Office.**

Sir,

With reference to your Limited Tender Notice No. F.42-1(7.9)/NIOS/Admn./Mtce dated / /2026, we are pleased to submit our quotation for the above-mentioned work. We hereby agree to execute the work as per the terms and specifications laid down in the NIT and Annexure A.

Please find enclosed the following documents:

1. Signed copy of NIT and acceptance of terms and conditions
2. Quotation with item-wise and total cost
3. Copy of PAN and GST registration copies
4. List of similar works executed along with work orders
5. Company profile
6. Declaration of acceptance of all terms and conditions
7. EMD in the form of FDR /Demand Draft/ Bank Guarantee MSME Certificate
8. Audited balance sheets or audit reports for the last three financial years.

We request you to kindly consider our offer.

Thanking you,

Yours faithfully,

(Authorized Signatory)

Name:

Designation:

Firm's Name:

Contact No.:

Seal:

Date:

Price Quotation Format

Subject: Repair of Kitchen, Provision of Washing Area and Creation of Partition for R&I Section in front of PRO Office.

	Description of Item	unit	qty	rate	Total
1	Making the opening in brick masonry including dismantling in floor or walls by cutting masonry and making good the damages to walls, flooring and jambs complete, to match existing surface including disposal of mulba/ rubbish to the nearest municipal dumping ground, all complete as per direction of Engineer-in-Charge	sqm	15		
2	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	cum	5		
3	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-inCharge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete (make somany / kajaria/orient bell)	sqm	50		
5	Dismantling tile work in walls, floors and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm	sqm	50		
6	Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge.	sqm	60		
7	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gram/litre, of approved manufacturer and of required shade and colour all complete to achieve even shade and colour (two or more coats) over and including water thinnable priming coat with cement primer having VOC content less than 50 gram/litre	sqm	500		
8	Finishing walls with ready mixed Premium acrylic emulsion paint (Company Depot Tinted) having VOC less than 50 gm/litre and UV resistance as per IS 15489:2004, Alkali & fungal resistance, dirt resistance exterior paint of required shade with silicon additives. Two or more coats applied @ 1.43 litre/ 10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm.	sqm	250		
9	Painting with aluminium paint of approved brand and manufacture to give an even shade One or more coats .	sqm	60		

10	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge	cum	2		
11	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	sqm	10		
12	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary lilling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass I stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows & ventilators including providing and lilling hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket 31. 1. I Powder coated aluminium (minimum thickness of powder coating 50 micron)	kg	30		
13	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary lilling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass I stainless steel screws, all complete as per architectural	kg	100		

	drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :for fixed portion :Powder coated aluminium (minimum thickness of powder coating 50 micron)				
14	Providing and fixing 2-3 mm thick Aluminium Composite Panel (ACP).	sqm	33		
15	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge .(Cost of aluminium snap beading shall be paid in basic item):With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	sqm	25		
16	Filling the gap in between aluminium frame & adjacent RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.Upto 5 mm depth and 5 mm width	m	50		
17	Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm long with SS screws etc .complete as per direction of Engineer-in-Charge Polyester powder coated minimum thickness 50 micron aluminium tubular handle bar	each	6		
18	Providing and fixing Brass 100 mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	each	4		
19	Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISi, IS : 3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.	each	3		
20	supply and fixing of 100mm pvc pipe including all fitting completeThis includes jointing of pipes & fittings with one step PVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete	m	25		

21	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:6 (1 cement : 6 coarse sand) : With F.P.S.(non modular) bricks	cum	1		
22	Providing and fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS:13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required : Kitchen sink with drain board 510x1040 mm bowl depth 225 mm	each	2		
23	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings and fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc 20 mm nominal dia Pipes	m	45		
24	Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms. 15 mm nominal bore	each	2		
25	Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete	each	2		
26	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15 mm nominal bore	each	2		
27	Supplying, installing, testing, and commissioning of wall-mounted commercial kitchen exhaust chimney system complete as per specifications below (unit: each): Hood: SS 304 grade, 18-20 gauge (1.0-1.2 mm thick), rectangular canopy type, length 6-8 ft (specify 7 ft), width 3 ft, height 1.5-2 ft, #4 polished finish, with pre-wired LED lights (1 per 5 ft). Filters: SS baffle grease filters (washable, 25" high equivalent), with grease cup and drip tray. Exhaust Fan: metal exhaust fan 600mm crompton Ducting: SS/GI rectangular ducts (300x150 mm), 20-30 ft length with bends, insulated, including supports and exhaust collar (10-24" based on length). Installation: At 6.5-7 ft height from floor, with 3" standoff brackets, fire-safe per NFPA 96 equivalent, centrally above cooking range.	each	1		

28	Constructing brick masonry manhole in cement mortar 1:4 (1 cement : 4 coarse sand) with R.C.C. top slab with 1:1.5:3 mix (1 cement : 1.5 coarse sand (zone-III) : 3 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design : Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) :With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	each	1		
----	---	------	---	--	--

Total Amount (including all applicable taxes): ₹ _____

Amount in Words: Rupees _____ only.

I/We certify that the rates quoted are inclusive of all taxes, transportation, and installation charges, and are valid for 60 days from the date of submission.

Authorized Signatory
(Signature & Seal)

Declaration of Acceptance of Terms & Conditions

Declaration

I/We have read and understood the terms and conditions mentioned in the NIT issued by National Institute of Open Schooling for **Repair of Kitchen, Provision of Washing Area and Creation of Partition for R&I Section in front of PRO Office**. I/We hereby declare that all the terms and conditions of the tender are acceptable to us without any deviation.

Date: _____

Place: _____

Authorized Signatory
(Signature & Seal)

List of Similar Works Executed (Past Experience)

Sl. No.	Client Name	Description of Work	Work Order No. & Date	Completion Date	Value (₹)	Status
1						
2						
3						

Note: Enclose copies of work orders or completion certificates for each listed project.

Date: _____

Place: _____

Authorized Signatory
(Signature & Seal)

Company Profile (Basic Details)

Company Name:

Registered Address:

Year of Establishment:

Type of Firm (Proprietorship/Partnership/Pvt Ltd etc.):

Authorized Contact Person:

Phone:

Email:

GST No.:

PAN No.:

Bank Details (for payment):

- Bank Name:
- Account No.:
- IFSC Code:

Date: _____

Place: _____

Authorized Signatory
(Signature & Seal)

:

